




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 11/06, H04L 25/14		A1	(11) International Publication Number: WO 99/20033
		(43) International Publication Date:	22 April 1999 (22.04.99)
(21) International Application Number: PCT/US98/05587		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 March 1998 (23.03.98)		Published <i>With international search report.</i>	
(30) Priority Data: 08/951,151 15 October 1997 (15.10.97) US			
(71) Applicant: NETSPEED, INC. [US/US]; 12303 Technology Boulevard, Austin, TX 78727 (US).			
(72) Inventors: LOCKLEAR, Robert, H., Jr.; 11027 Crossland Drive, Austin, TX 78726 (US). CANTRELL, Craig, S.; 6102 Northern Dancer, Austin, TX 78746 (US). McCLANAHAN, Kip, R.; 3112 Kerbey Lane, Austin, TX 78703 (US).			
(74) Agent: SHOWALTER, Barton, E.; Baker & Botts, L.L.P., 2001 Ross Avenue, Dallas, TX 75201-2980 (US).			

(54) Title: DATA COMMUNICATION USING A MODIFIABLE NUMBER OF XDSL MODEMS

(57) Abstract

A communication system includes a number of communication devices (12) coupled to a data network (14) using communication servers (16). The communication system supports communication sessions between a variety of networks and devices using, at least in part, XDSL communication techniques. Specifically, information associated with a session passes between a device (12) and an associated server (16) using a modifiable number of XDSL modems and associated twisted pair lines (22).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DATA COMMUNICATION USING A MODIFIABLE
NUMBER OF XDSL MODEMS

TECHNICAL FIELD OF THE INVENTION

The invention relates in general to data communication, and more particularly to data communication using a modifiable number of XDSL modems.

5

BACKGROUND OF THE INVENTION

A communication server provides access to communication facilities. For example, a communication server having a bank of modems may provide subscriber access to the modems for data communication. A communication server may be associated with its own dedicated network or with an existing network, such as the public switched telephone network (PSTN).

As networks provide greater connectivity and access to information, there is an increasing demand for data communication at higher rates. For example, Internet sessions may require high data rates to accommodate multimedia information. One solution to provide increased data rates replaces existing twisted pair wiring with high bandwidth media, such as coaxial cable or fiber optic links. Other solutions adopt improved transmission techniques using the existing hardware infrastructure. For example, digital subscriber line (XDSL) technology provides higher bandwidth data service over existing twisted pair wiring.

Data rates supported by a single XDSL line may still be inadequate for demands. One solution involving integrated services digital network (ISDN) bundles multiple lines with the same data rate to increase data capacity for a session. However, this known technique lacks the flexibility or intelligence to provide reliable and economical high bandwidth data communication service using XDSL technology.

10 SUMMARY OF THE INVENTION

In accordance with the present invention, the disadvantages and problems associated with data communication have been substantially reduced or eliminated. The present invention provides a communication system that modifies the number of XDSL modems for communicating data in response to loading information and threshold information.

In accordance with one embodiment of the present invention, a communication system for communicating data associated with a session includes a number of twisted pair lines. A first communication device has a number of first XDSL modems coupled to the twisted pair lines. The first communication device communicates data associated with the session using the twisted pair lines. A second communication device has a number of second XDSL modems coupled to the twisted pair lines that communicate with the first XDSL modems. The second communication device determines the number of second XDSL modems for communicating data associated with the session based on loading information and corresponding threshold information of at least one of the second XDSL modems.

In accordance with another embodiment of the present invention, a communication device for communicating data associated with a session using a number of twisted pair

lines includes a number of XDSL modems coupled to the twisted pair lines. The communication device also includes an interface and a router for communicating data between the interface and the second XDSL modems. A controller
5 coupled to the XDSL modems and the router receives loading information from at least one of the XDSL modems, compares the loading information to stored threshold information, and determines the number of XDSL modems for communicating data associated with the session.

10 In accordance with another embodiment of the present invention, a method for communicating data using a number of XDSL modems coupled to a number of associated twisted pair lines includes: determining loading information of at least one XDSL modem; comparing the loading information to
15 threshold information; and determining the number of XDSL modems for communicating data associated with a session in response to the comparison.

Still another embodiment of the present invention includes a method of segmenting a packet of data for
20 communication by a number of XDSL modems, the method comprising: receiving a packet; determining the size of the packet; and segmenting the packet into subpackets based on proportionality factors associated with the XDSL modems to communicate the subpackets.

25 Important technical advantages of the present invention include a communication device that modifies the number of XDSL modems used in a session. The modification is accomplished by comparing loading information with corresponding threshold information associated with the
30 data rate capacity of the XDSL modems. If the data rate increases to a predetermined percentage (e.g., 80%) of the capacity of an XDSL modem, the communication device requests service from another XDSL modem. Similarly, if the data rate decreases to a predetermined percentage

(e.g., 30%) of the capacity of the XDSL modem and more than one XDSL modems are servicing the session, the communication device requests suspension or termination of service from a selected XDSL modem. The communication device may then support a session having a range of data rate needs while optimizing the use of a number of XDSL modems.

Another important technical advantage of the present invention includes the selection of lines based on a variety of characteristics and factors, such as: different upstream and/or downstream data rate capacities, varying times needed to prepare the line for data communication, cost to operate the lines, minimum billing increments for line usage, and other operational parameters. The communication device maintains an activity table to determine status information on twisted pair lines and XDSL modems. In one embodiment, the table contains information on the minimum time each modem should be active for efficient use, the actual time each modem has been in an active state, a priority rank for each modem, fixed and/or adjusted data rate capacity, threshold values to remove or add a modem, and loading information detailing current data rates (e.g., packet rate, bit rate, error rate).

Another important technical advantage of the present invention includes the segmenting of data in proportion to the data rate capacity of active modems. After receiving a data packet from a network, one embodiment of the present invention determines the packet size and then divides the packet into subpackets based on proportionality factors derived from the capacity of active modems serving the session. The communication device addresses the subpackets using virtual circuits supported by a suitable multipoint protocol. Proportionality factors may change dynamically with modifications to the number of modems in active use

and adjustments in the current data rate capacity of the modems. Other important technical advantages are readily apparent to one skilled in the art from the following figures, descriptions, and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and for further features and advantages, reference is now made to the following description, taken in conjunction with the accompanying drawings, in which:

FIGURE 1 illustrates a communication system in accordance with the present invention;

FIGURE 2 illustrates in greater detail a communication device of the communication system of FIGURE 1;

FIGURE 3 illustrates in greater detail a communication server of the communication system of FIGURE 1;

FIGURE 4 is a table that includes loading information, threshold information, and operating parameters of modems in the communication system of FIGURE 1;

FIGURE 5 is a flowchart of a method for modifying the number of modems for communicating data in response to loading information and threshold information;

FIGURE 6 is a flowchart of a method for segmenting a data packet in the communication system of FIGURE 1; and

FIGURE 7 is a diagram illustrating a particular method for determining a data rate in the communication system of FIGURE 1.

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 illustrates a communication system 10 that includes a number of communication devices 12 coupled to a data network 14 using communication servers 16. In general, communication system 10 supports communication sessions between a variety of networks and devices using, at least in part, XDSL communication techniques. Specifically, information associated with a session passes between device 12 and server 16 using a modifiable number of XDSL modems and associated twisted pair lines 22.

Throughout this description, device 12 and server 16 may be referred to generally as communication devices.

5 A variety of local area networks (LANs) 18 couple to devices 12. LAN 18 couples terminals 20 together for a variety of functions including communication among terminals 20. Terminals 20 include computers, workstations, printers, scanners, facsimile machines, or other computing or communicating devices that operate to communicate information using LAN 18. LAN 18 may be
10 located at corporate or consumer premises, and serves a number of terminals 20. LAN 18 comprises a token ring, Ethernet, or other network or interconnection of terminals 20, and may also comprise a portion of a wide area network (WAN). LAN 18 supports Ethernet (10 Mbps), Fast Ethernet
15 (100 Mbps), Gigabit Ethernet, switched Ethernet, fiber distributed data interface (FDDI), asynchronous transfer mode (ATM), or any other suitable networking protocol or technology. LAN 18 couples to data network 14 using server 16, device 12, or any suitable combination of server 16 and
20 device 12.

Device 12 couples to server 16 using a number of twisted pair lines 22. Lines 22 may comprise wiring that is commonly installed at subscriber premises and as the local loop in many public switched telephone networks
25 (PSTNs). Lines 22 may be unshielded twisted pair (UTP), shielded twisted pair (STP), or other suitable type or category of wiring made of copper or suitable conductive material. In one embodiment, device 12 and server 16 support high bandwidth data service in the local loop using
30 asymmetric digital subscriber line (ADSL) technology, high bandwidth digital subscriber line (HDSL) technology, very high bandwidth digital subscriber line (VDSL) technology, or other suitable high bandwidth technology.

U.S. Patent No. 5,668,857 describes in detail the architecture and operation of one embodiment of server 16, and is hereby incorporated by reference for all purposes. Server 16 may be located at a central office, remote terminal, or any other location that terminates twisted pair lines 22. Server 16 contemplates any number of couplings to devices 12 using any number of twisted pair lines 22. For example, server 16 may couple to a first device 12 using a single twisted pair line 22 and to a second device 12 using multiple twisted pair lines 22.

One embodiment of server 16 couples to a central office (CO) 24, which in turn couples to the public switched telephone network (PSTN) 26 to provide traditional plain old telephone service (POTS) or other networked communication services supported by PSTN 26. Server 16 may include an active or passive splitter or other device to provide a voice path to PSTN 26 through CO 24 and a data path to data network 14. Using frequency division multiplexing or other suitable technique, server 16 provides simultaneous voice and data service to device 12.

Server 16 couples to data network 14 which, depending on the embodiment, supports asynchronous transfer mode (ATM), frame relay, X.25, or other suitable data communication protocol or technology. Data network 14 couples one or more servers 16 for communicating data to and from a number of LANs 18. Data links 28 between server 16 and data network 14 may be T1, T3, E1, E3, or other high bandwidth links using wireline or wireless techniques.

A particular embodiment of server 16, designated server 17, couples terminals 20 serviced by LAN 18a to data network 14 without the use of twisted pair lines 22. Server 17 includes appropriate protocols to support virtual channels and multiple communication paths between itself

and devices 12 in communication system 10. For example, server 17 may support an ATM layer, a multilink point-to-point protocol layer, and an Internet Protocol (IP) layer to communicate with devices 12.

5 In operation, communication system 10 establishes a session for communicating data between one or more terminals 20 or devices 12 in communication system 10. For example, communication system 10 may establish a session between terminal 20a serviced by LAN 18a and terminal 20b serviced by LAN 18b. Communication for such a session would pass through one or more twisted pair lines 22 associated with device 12 servicing LAN 18b. Communication for a session between, for example, terminal 20c serviced by LAN 18c and device 12a would pass through one or more twisted pair lines 22 associated with device 12 servicing LAN 18c and one or more twisted pair lines 22 associated with device 12a. Also, communication system 10 supports communication between device 12 and/or terminal 20 and another device integral to or coupled to data network 14, such as server 17, an Internet server, an Internet service provider (ISP), a corporate server, an on-line service provider, or other high bandwidth communication device. The communication path for each session supported by communication system 10 includes at least one span of one or more twisted pair lines 22.

25 To initiate a session, terminal 20 serviced by LAN 18 sends a signal to device 12. Alternatively, device 12 initiates its own session without signaling from LAN 18 or terminal 20. Device 12 identifies one or more twisted pair lines 22 that are available to communicate data with server 16. For each twisted pair line 22 identified for the session, device 12 communicates a request for service to server 16. The request for service may comprise a digital off-hook signal that causes server 16 to select a modem in

its modem pool. The off-hook detector at server 16 may monitor direct current voltages, electrical tones, data link frames, or any other protocol or data sequencing to determine whether device 12 needs data access. The off-hook detector in server 16 may monitor electrical tones generated by a modem at device 12 while in the process of training, notching, equalizing, or performing any other task that puts electrical tones onto twisted pair lines 22. Server 16 may also detect frames or packets. These frames or packets could be Ethernet, ATM, HDLC, or any suitable data communications frame format. The off-hook detector in server 16 could also examine various protocols such as Transmission Control Protocol/Internet Protocol (TCP/IP), a multilink point-to-point protocol (PPP), or any other suitable network protocol or data stream.

Server 16 responds to the request for service by selecting an available modem in its modem pool, retrieving stored line characteristics, training the associated twisted pair line 22 for communication, and establishing XDSL communication protocols. Server 16 communicates an acknowledgment to device 12 during or upon establishment of XDSL communication. Server 16 then communicates a connect request message to data network 14, which is then propagated to the destination device 12 or terminal 20. Communication system 10 builds the communication path from originating device to destination device on a segment-by-segment basis using a series of connect request and acknowledgment messages.

Once the communication path is set up, the participating elements of communication system 10 operate to exchange information associated with a session. In a particular embodiment, the originating terminal 20 communicates data to device 12 using LAN 18. Device 12 converts the data into a protocol consistent with

communication over twisted pair lines 22, and sends the data to server 16 over one or more active lines 22. Server 16 converts the data into a protocol consistent with communication in data network 14, and sends the data using links 28 to data network 14. Data network 14 then communicates the data using links 28 to server 16 associated with the destination device 12, LAN 18, and/or terminal 20. Alternatively, data network 14 communicates the data to server 17 for delivery to a selected terminal 20 serviced by LAN 18a.

An important technical advantage of the present invention is the establishment and maintenance of a communication session that includes at least one segment of communication between server 16 and device 12 using a modifiable number of twisted pair lines 22. In a particular embodiment, device 12 and/or server 16 monitor the loading information on active modems associated with the session, compare the loading information to threshold information on the modems, and add or remove lines from active service as needed. Adding twisted pair line 22 to active service when data traffic is heavy and removing twisted pair line 22 from active service when data traffic is lower allows device 12 and server 16 to operate at higher bandwidths only when needed. Such operation optimizes the use of XDSL modems in device 12 and server 16.

FIGURE 2 illustrates in greater detail device 12 of communication system 10. Device 12 includes modems 50 coupled to twisted pair lines 22. Modems 50 transmit and receive data using any suitable digital subscriber line technology, such as ADSL, VDSL, or HDSL, referred to generally as XDSL. Each modem 50 includes an associated twisted pair line 22 and data line 54. In operation, modem 50 receives inbound or downstream communication from server

16 on twisted pair line 22, and places the resulting data in an appropriate protocol on data line 54 for delivery to router 52. Modem 50 also receives outbound or upstream communication on data line 54, and prepares the data for delivery to server 16 using twisted pair line 22.

Router 52 couples data lines 54 from modems 50 to a series of protocol layers. Protocol layers are arranged in a first stack 56 associated with XDSL communications and a second stack 57 associated with LAN communications. Router 52 performs open systems interconnect (OSI) model processing by passing data through protocol layers associated with stacks 56 and 57. Generally, router 52 supports any suitable number of protocols to allow communication between server 16 and LAN 18.

In a particular embodiment, lines 54 couple to a first physical layer 58, such as an ADSL physical layer, which in turn couples to an intermediate protocol layer 60, such as a multilink point-to-point protocol (PPP). A common protocol layer 62, such as an Internet Protocol (IP) layer, provides a common protocol between first stack 56 and second stack 57. Common protocol layer 62 in second stack 57 couples to an intermediate protocol layer 64, such as a media access controller (MAC) layer. Intermediate protocol layer 64 couples to a second physical layer 66, such as an Ethernet physical layer, which in turn couples to an interface 68 using line 70.

In a specific embodiment, intermediate protocol layer 60 supports multiple switched virtual circuits (SVCs) or permanent virtual circuits (PVCs). Using virtual circuits, device 12 can support a communication session that uses more than one modem 50. This is accomplished by servicing a session with two or more virtual circuits, where each virtual circuit is associated with modem 50 and its corresponding twisted pair line 22.

Interface 68 couples device 12 to LAN 18. Interface 68 supports any suitable technology or protocol that provides communication between LAN 18 and router 52. The selection and design of interface 68 may depend on the type or functionality of LAN 18, as well as the data service rate supported by LAN 18 and device 12. Also, in a particular embodiment where device 12 is not associated with LAN 18, interface 68 supports direct communication with components internal or external to device 12.

Controller 72 accesses modems 50 using control line 71 and router 52 using control line 73. Controller 72 manages the overall operation of device 12 by collecting information from modems 50 and router 52, making decisions based on this information and other stored information, and directing the operation of components of device 12 in response to these decisions. Controller 72 also accesses database 74 to store, retrieve, and maintain loading information 76, threshold information 78, operating parameters 80, line information 82, program information 84, and session information 86. FIGURE 4, discussed below, describes contents of database 74 in greater detail. Information shown in database 74 may reside in different components of device 12 or in components external to device 12. In one embodiment, controller 72 includes a timer 88 to manage the use of modems 50, as described below. Controller 72 may also couple to LAN 18 or other external components using line 90.

In operation, device 12 receives inbound or downstream data associated with a session on one or more modems 50 coupled to twisted pair lines 22, passes the data through protocol layers of router 52, and communicates the data through interface 68 to LAN 18. Device 12 also receives outbound or upstream data associated with the session from LAN 18 through interface 68, passes the data through

protocol layers of router 52, and communicates the data through one or more modems 50 to twisted pair lines 22. During this process, controller 72 may also maintain loading information 76 and threshold information 78 in database 74 and compares loading information 76 to threshold information 78 to determine which modems 50 to activate or inactivate.

Controller 72 also maintains operating parameters 80, line information 82, program information 84, and session information 86 in database 74. Operating parameters 80 include modem priorities, minimum times to activate modems 50 for optimum use, and proportionality factors to perform data packet segmentation. Line information 82 may include amplitude, phase, timing, delays, impedance, and/or other data characterizing the electrical or physical properties of twisted pair lines 22. Program information 84 may include instructions, parameters, data, and other information used by controller 72. Session information 86 may include virtual circuit addresses and modem assignments for each session serviced by device 12.

FIGURE 3 illustrates in greater detail communication server 16 of communication system 10. Server 16 includes switch 100, which couples twisted pair lines 22 to modem pool 104 using lines 102. Modems 50 in modem pool 104 are of similar design and operation as modems 50 in device 12 and convert signals in an appropriate XDSL communication protocol into digital data in an appropriate digital protocol. Modems 50 pass the converted signals to a switching fabric 106 using lines 108. Switching fabric 106 may be any type of switch in hardware and/or software that communicates information between modems 50 and interface 110. As taught in U.S. Patent No. 5,668,857, controller 114 directs switch 100 to couple a selected subset of twisted pair lines 22 to selected output lines 102 that

couple to modems 50 in modem pool 104. Controller 114 also receives loading information 76 and threshold information 78 from modems 50 in modem pool 104.

Switching fabric 106 establishes a session and assigns
5 an address (e.g., virtual path, virtual channel) to be used in future communications associated with the session. Switching fabric 106 and/or controller 114 store session, address, and mapping information as session information 86 in database 116. For inbound or downstream communication,
10 switching fabric 106 directs communications from data network 14 that include the address associated with the established session to an assigned or designated modem 50. For outbound or upstream communication, switching fabric 106 directs communications from active modems 50 in modem
15 pool to data network 14. In one embodiment, switching fabric 106 is an asynchronous transfer mode (ATM) switching fabric which communicates data between modem pool 104 and interface 110 using line 112. Interface 110 includes hardware and/or software to support communication between
20 data network 14 and switching fabric 106.

Controller 114 accesses switch 100, modem pool 104, switching fabric 106, and interface 110 to control the overall operation of server 16. Controller 114 also accesses database 116 to store, retrieve, and maintain
25 loading information 76, threshold information 78, operating parameters 80, line information 82, program information 84, and session information 86. Information shown in database 116 may also reside in different components of server 16 or in components external to server 16. For example,
30 switching fabric 106 may store locally one or more items shown in database 116.

In operation, server 16 receives inbound or downstream data associated with a session from data network 14 at interface 110 coupled to line 28, passes the data to one or

more modems 50 in modem pool 104 servicing the session using switching fabric 106, and communicates the data from modems 50 to associated twisted pair lines 22 through switch 100. Server 16 also receives outbound or upstream data associated with the session on one or more modems 50 coupled to switch 100 and twisted pair lines 22, and passes the data through switching fabric 106 to interface 110 for transmission to data network 14. During this process, controller 114 may also maintain loading information 76 and threshold information 78 in database 116 and compares this loading information 76 to threshold information 78 to determine which modems 50 in modem pool 104 to activate or inactivate.

FIGURE 4 is a table 200 which includes in more detail particular data contained at device 12 and/or server 16 of communication system 10. Table 200 may include loading information 76, threshold information 78, operating parameters 80, and session information 86 for each modem 50 of device 12 or server 16 to perform both inbound or downstream communication and outbound or upstream communication. Table 200 includes columns 202, 204, 206, 208, 210, and 212 that contain information on modems 1, 2, 3, 4, 5, and 6 respectively. Table 200 may include any number of columns to represent any number of modems 50 in device 12 or server 16. The following description refers to the operation of device 12, but applies to a similar operation performed at server 16.

Each column in table 200 contains two subcolumns: column A representing outbound or upstream data (i.e., data from device 12 to data network 14), and column B representing inbound or downstream data (i.e., data from data network 14 to device 12). For example, column 202 representing modem 1 comprises column 202A representing upstream information for modem 1, and column 202B

representing downstream information for modem 1. Some information maintained in table 200 (e.g., modem priority 224, minimum time up 226, total time up 228, and session identifier 232) do not distinguish between upstream and downstream operation.

Loading information 76 in table 200 includes a packet rate 213, bit rate 214, and an error rate 216. Packet rate 213 may be expressed in thousands of messages per second (Kmps) and indicates the number of messages, packets, cells, or other grouping of information (referred to collectively as messages) communicated by modem 50 each second. Bit rate 214 may be expressed in millions of bits per second (Mbps) and indicates the number of bits communicated by modem 50 each second. Error rate 216 represents the number of errors or error bits divided by total bits communicated by modem 50. For example, error rate 216 may be expressed as the number of errors in the data for every 10^7 bits received. A high error rate 216 may indicate malfunction or overtasking of modem 50.

Threshold information 78 in table 200 includes a data rate 218, an add percentage 220, and a remove percentage 222. Data rate 218 may be expressed in millions of bits per second (Mbps) and indicates the maximum data rate capacity upstream and downstream for each modem 50. For download intensive applications (e.g., Internet browsing, remote computing), downstream data rates 218 are greater than upstream data rates 218. Modems 50 may adjust data rate 218 dynamically based on error rate 216, line quality, noise levels, or other factors. Add percentage 220 indicates the percentage of data rate 218 at which device 12 activates another modem 50 for the session. For example, if modem 2 (column 204) operating on a session alone maintains a downstream data rate 218 above 6.8 Mbps — calculated from the product of downstream data rate 218

(column 204B, row 218) of 8 Mbps and add percentage 220 (column 204B, row 220) of eighty-five percent — device 12 activates modem 1 (column 202). In similar fashion, remove percentage 222 indicates the percentage of data rate 218 at which device 12 deactivates modem 50.

Operating parameters 80 in table 200 include modem priority 224, a minimum time up 226, a total time up 228, and a proportionality factor 230. Modem priority 224 indicates the order in which device 12 activates modems 50 to service a session. Prioritization of modems 50 allows device 12 to activate modems in an efficient manner because, due to varying modem and line characteristics, not all modems 50 and associated lines 22 cost the same to activate and/or operate. Some modems 50 cost less to activate than others and are suitable for shorter periods of activity or for sporadic periods of activity. Other modems 50 may work better for large, constant data rates because the cost to activate and operate one high data rate modem 50 over an extended period of time may be less than activating and operating several low data rate modems 50.

Minimum time up 226 indicates the minimum time that modem 50 should stay active for efficient use. Total time up 228 indicates the total time that each modem 50 has been in an active state. Proportionality factor 230 indicates the proportion of data in a session that modem 50 communicates for both upstream and downstream communications. For example, a current session supported by device 12 uses three modems 50 (modems 1, 2, and 5 represented in columns 202, 204, and 210, respectively) for communicating data. Each proportionality factor 230 (upstream and downstream) represents the associated data rate 218 for each modem 50 divided by the sum of data rates 218 for all modems 50 servicing the same session. For example, in table 200, modem 2 has a data rate 218 of 1Mbps

upstream and 8Mbps downstream, which is twice the corresponding data rates of 0.5Mbps upstream and 4Mbps downstream for modems 1 and 5. The sum of downstream data rates 218 for the three modems is 16Mbps. Thus, the downstream proportionality factor 230 for modem 1 is downstream data rate 218 for modem 1 (4Mbps) over the sum of downstream data rates 218 for the three modems (16Mbps), or 0.25. Device 12 or server 16 may calculate upstream proportionality factor 230 in a similar manner.

Session information 86 in table 200 includes a session identifier 232 and a routing address 234. Session identifier 232 indicates the session currently serviced by modems 50 represented in table 200. For example, modems 1, 2, and 5 service a first session, and modems 3 and 6 service a second session. In this example, modem 4 remains unassigned to any particular session. Routing address 234 may comprise addresses or identifiers associated with switched virtual circuits (SVCs), permanent virtual circuits (PVCs), or other communication protocol that supports multipoint capabilities. In a particular embodiment, each modem 50 represented in table 200 maintains routing addresses 234 for both upstream and downstream communications.

FIGURE 5 is a flowchart 300 depicting a method for modifying the number of modems 50 for communicating data in a session based on loading information 76 and threshold information 78. Although the following discussion describes flowchart 300 with respect to device 12, server 16 may perform a similar method. Communication system 10 contemplates device 12, server 16, or both performing the load balancing operations described in flowchart 300.

Flowchart 300 begins at step 302 where device 12 selects an active modem 50 associated with a current communication session supported by device 12. Device 12

then retrieves loading information 76 from selected modem 50 in step 304. Device 12 may operate on this loading information 76 immediately, or maintain this loading information 76 in database 74 for later use. Device 12 computes a downstream add threshold (ADD_DOWN), an upstream add threshold (ADD_UP), a downstream remove threshold (REM_DOWN), and an upstream remove threshold (REM_UP) at step 305 as follows:

```
10      ADD_DOWN = downstream add percentage
      220 * downstream data rate 218;
      ADD_UP = upstream add percentage 220 *
      upstream data rate 218;
      REM_DOWN = downstream remove percentage
15      222 * downstream data rate 218; and
      REM_UP = upstream remove percentage 222
      * upstream data rate 218.
```

Device 12 performs steps 306-312 to determine whether there is a need to activate another modem 50 or deactivate the selected modem 50. Device 12 compares upstream loading information 76 (UP) to ADD_UP at step 306 and downstream loading information 76 (DOWN) to ADD_DOWN at step 308. UP may comprise any measure of the upstream loading of the selected modem 50, such as packet rate 213, bit rate 214, and error rate 216 in columns 202A, 204A, 206A, etc. Similarly, DOWN may comprise any measure of the downstream loading of the selected modem 50, such as packet rate 213, bit rate 214, and error 216 in columns 202B, 204B, 206B, etc.

If either threshold is exceeded as determined at steps 306 or 308, device 12 selects an inactive modem 50 at step 314 and accesses corresponding line information 82 stored in database 74 to train the associated twisted pair line 22

in preparation for communication at step 316. Before, during, or after training twisted pair line 22, the selected inactive modem 50 communicates a request for service to server 16 at step 318, and receives an acknowledgment at step 320. In a particular embodiment, server 16 communicates an acknowledgment to device 12 upon determining loading characteristics of modems 50 in modem pool 104, selecting an available modem 50, establishing a connection using switch 100 and twisted pair line 22 between the available modem 50 at server 16 and the selected modem 50 at device 12, and successfully training twisted pair line 22 to support communication. Upon receiving an acknowledgment that server 16 can support communication on the selected modem 50, device 12 tags the selected modem 50 as active at step 322 and starts timer 88 at step 324, marking the start of active state. Device 12 updates proportionality factors 230 at step 326 to reflect the addition of modem 50 to service the session, and flowchart 300 proceeds to step 302.

If neither threshold is exceeded in steps 306 and 308, device 12 compares upstream loading information 76 (UP) to REM_UP and downstream loading information 76 (DOWN) to REM_DOWN at step 312. If both threshold floors are met at step 312, device 12 determines whether it may remove the selected modem 50 or another modem 50 servicing the session at step 330. The determination of which modem to remove may depend on modem priority 224, data rate 218, or other factors. The determination of the appropriate modem to be removed or deactivated at step 330 also contemplates the situation where the selected modem 50 is the only remaining modem servicing the session, and therefore will not be removed before session termination. If total time up 228 for modem 50 to be deactivated is greater than or equal to minimum time up 226 at step 332, modem 50 communicates a

request to end modem service at step 334. Upon receiving an acknowledgment from server 16 at step 336, device 12 tags modem 50 as inactive at step 338. Device 12 updates proportionality factors 230 at step 326 to reflect the removal of modem 50, and flowchart 300 proceeds to step 302.

FIGURE 6 is a flowchart 400 depicting a method for segmenting a data packet into subpackets for communication by modems 50. The data packet may comprise any organization of information received by device 12 for upstream communication over two or more twisted pair lines 22. The techniques performed in flowchart 400 may be implemented in protocol layers supported by router 52, controller 72, or a combination of operations between router 52 and controller 72. Although the following discussion describes flowchart 400 with respect to device 12, server 16 may perform a similar method.

Flowchart 400 begins at step 402 where device 12 receives a data packet. Device 12 then determines the packet size at step 404 and segments the data packet into subpackets based on proportionality factors 230 of active modems 50 at step 406. Referring to the example illustrated by table 200 of FIGURE 4, device 12 would split a data packet associated with session one into three different subpackets for communication by modems 1, 2, and 5. If the packet size is one thousand bytes, then device 12 would split the data packet into a first subpacket of two hundred and fifty bytes for communication by modem 1, a second subpacket of five hundred bytes for communication by modem 2, and a third subpacket of two hundred and fifty bytes for communication by modem 5. Device 12 addresses the subpackets for communication at step 408 by respective modems 50. During operation of device 12, proportionality factors 230 may change due to the addition and/or removal

of modems 50 and the modification of data rates 218 supported by modems 50, as indicated at step 410. If proportionality factors 230 change, device 12 updates proportionality factors 230 at step 412 in preparation for receiving the next data packet.

FIGURE 7 is a diagram illustrating a particular method for determining loading information 76 (e.g., packet rate 213, bit rate 214, error rate 216, etc.) for modem 50 in communication system 10. Device 12 and/or server 16 may adopt this method for both upstream and downstream communications. The following description illustrates the technique to determine downstream loading information 76 for modem 50 in device 12.

Controller 72 in device 12 retrieves downstream loading information 76 of modem 50 over a number of successive intervals 500. Each interval 500 corresponds to loading information 76 experienced by modem 50 over a particular interval of time Δt . Loading information 76 gathered by controller 72 for each interval 500 may comprise packet rate 213, bit rate 214, error rate 216, or other loading measure that represents the peak, average, or other measure of activity of modem 50 during interval 500.

Controller 72 then groups intervals 500 into windows 502. Each window 502 represents a suitable combination of loading information 76 over a predetermined number of intervals 500. Controller 72 generates successive windows 502 of loading information 76 by shifting in time the grouping of intervals 500 for each successive window 502. This "sliding window" technique allows controller 72 to add or remove modems 50 based on trends in loading information 76. For example, controller 72 may determine whether to add or remove a modem based on whether the average and/or maximum loading information 76 gathered for each interval 500 in window 502 exceeds or falls below threshold

information 78. Controller 72 may also require a succession of windows 502 to indicate the desire to add or remove modems 50.

5 Although the present invention has been described in
several embodiments, a myriad of changes, variations,
alterations, transformations and modifications may be
suggested to one skilled in the art, and it is intended
that the present invention encompass such changes,
10 variations, alterations, transformations and modifications
as fall within the spirit and scope of the appended claims.

WHAT IS CLAIMED IS:

1. A communication system for communicating data associated with a session, comprising:

a plurality of twisted pair lines;

5 a first communication device having a plurality of first XDSL modems coupled to the twisted pair lines, the first communication device operable to communicate data associated with the session using the twisted pair lines; and

10 a second communication device having a plurality of second XDSL modems coupled to the twisted pair lines and operable to communicate with the first XDSL modems, wherein the second communication device determines the number of second XDSL modems for communicating data associated with
15 the session based on loading information and corresponding threshold information of at least one of the second XDSL modems.

2. The communication system of Claim 1, wherein the
20 second communication device comprises:

a network interface;

a router for communicating data between the network interface and the second XDSL modems; and

25 a controller coupled to the second XDSL modems and the router, wherein the controller receives the loading information from at least one of the second XDSL modems, compares the loading information to stored threshold information, and determines the number of second XDSL
30 modems for communicating data associated with the session.

3. The communication system of Claim 1, wherein the first communication device further comprises a switch coupled to the twisted pair lines and the first XDSL modems, the switch operable to couple each twisted pair line to a selected first XDSL modem in response to a request received on the twisted pair line.

4. The communication system of Claim 1, wherein:
the first XDSL modems communicate information to the second XDSL modems at a first rate; and
the second XDSL modems communicate information to the first XDSL modems at a second rate less than the first rate.

5. The communication system of Claim 1, wherein loading information comprises a plurality of data rates over successive intervals of time, wherein each data rate is compared to the threshold information to determine the number of second XDSL modems for communicating data associated with the session.

6. The communication system of Claim 1, wherein loading information and corresponding threshold information for each second XDSL modem further comprises:

5 a downstream data rate for data received by the second XDSL modem;

an upstream data rate for data communicated by the second XDSL modem;

an upstream add threshold for comparison to the upstream data rate;

10 an upstream remove threshold for comparison to the upstream data rate;

a downstream add threshold for comparison to the downstream data rate; and

15 a downstream remove threshold for comparison to the downstream data rate.

7. The communication system of Claim 1, wherein the second communication device is operable to communicate a request for service upon determining to add another second
20 XDSL modem.

8. The communication system of Claim 1, wherein the first communication device is located at a central office.

25 9. The communication system of Claim 1, wherein the twisted pair lines each form a local loop between the first communication device and the second communication device.

10. A communication device for communicating data associated with a session using a plurality of twisted pair lines, the device comprising:

5 a plurality of XDSL modems coupled to the twisted pair lines;

an interface;

a router for communicating data between the interface and the XDSL modems; and

10 a controller coupled to the XDSL modems and the router, wherein the controller receives loading information from at least one of the XDSL modems, compares the loading information to stored threshold information, and determines the number of XDSL modems for communicating data associated with the session.

15 11. The device of Claim 10, wherein loading information comprises a plurality of data rates over successive intervals of time, wherein each data rate is compared to the threshold information to determine the
20 number of XDSL modems for communicating data associated with the session.

12. The device of Claim 10, wherein loading information and corresponding threshold information for each XDSL modem further comprises:

5 a downstream data rate for data received by the XDSL modem;

an upstream data rate for data communicated by the XDSL modem;

an upstream add threshold for comparison to the upstream data rate;

10 an upstream remove threshold for comparison to the upstream data rate;

a downstream add threshold for comparison to the downstream data rate; and

15 a downstream remove threshold for comparison to the downstream data rate.

13. The device of Claim 10, wherein the XDSL modems receive information at a first rate and transmit information at a second rate less than the first rate.

20

14. The device of Claim 10, wherein the device communicates a request for service upon determining to add another XDSL modem.

25

15. The device of Claim 10, wherein the router performs open systems interconnect (OSI) model processing of data communicated between the interface and the XDSL modems.

16. A communication device for communicating data using a plurality of twisted pair lines, the device comprising:

a plurality of XDSL modems;

5 a first switch coupled to the plurality of XDSL modems, the first switch operable to couple selected twisted pair lines to the XDSL modems;

an interface;

10 a second switch for communicating data between the XDSL modems and the interface; and

a controller coupled to the XDSL modems, wherein the controller modifies the number of XDSL modems for communicating data associated with the session based on loading information and corresponding threshold information
15 of at least one of the XDSL modems.

17. The device of Claim 16, wherein loading information comprises a plurality of data rates over successive intervals of time, wherein each data rate is
20 compared to the threshold information to determine the number of XDSL modems for communicating data associated with the session.

18. The device of Claim 16, wherein loading information and corresponding threshold information for each XDSL modem further comprises:

5. a downstream data rate for data received by the XDSL modem;

an upstream data rate for data communicated by the XDSL modem;

an upstream add threshold for comparison to the upstream data rate;

10. an upstream remove threshold for comparison to the upstream data rate;

a downstream add threshold for comparison to the downstream data rate; and

15. a downstream remove threshold for comparison to the downstream data rate.

19. The device of Claim 16, wherein the XDSL modems receive information at a first rate and transmit information at a second rate greater than the first rate.

20

20. The device of Claim 16, wherein the device communicates a request for service upon determining to add another XDSL modem.

25

21. The device of Claim 16, wherein the first switch comprises a cross-point matrix switch.

22. The device of Claim 16, wherein the device is located at a central office.

5 23. The device of Claim 16, wherein the second switch comprises a switching fabric coupled to the XDSL modems, wherein the switching fabric combines data received from the XDSL modems into a single data stream for communication by the interface.

24. A method for communicating data using a plurality of XDSL modems coupled to a plurality of associated twisted pair lines, the method comprising:

5 determining loading information of at least one XDSL modem;

comparing the loading information to threshold information; and

10 determining the number of XDSL modems for communicating data associated with a session in response to the comparison.

25. The method of Claim 24, wherein determining the number of XDSL modems for communicating data associated with a session further comprises:

15 adding an XDSL modem if the loading information exceeds corresponding threshold information; and

removing an XDSL modem if the loading information falls below corresponding threshold information.

26. The method of Claim 24, wherein loading information and corresponding threshold information for each XDSL modem further comprises:

5 a downstream data rate for data received by the XDSL modem;

an upstream data rate for data communicated by the XDSL modem;

an upstream add threshold for comparison to the upstream data rate;

10 an upstream remove threshold for comparison to the upstream data rate;

a downstream add threshold for comparison to the downstream data rate; and

15 a downstream remove threshold for comparison to the downstream data rate.

27. The method of Claim 24, wherein the loading information further comprises a packet rate, a bit rate, or an error rate.

28. The method of Claim 24, wherein determining the number of XDSL modems for communicating data associated with the session further comprises:

25 adding an XDSL modem if an upstream data rate exceeds an upstream add threshold or a downstream data rate exceeds a downstream add threshold; and

removing an XDSL modem if the upstream data rate falls below an upstream remove threshold and the downstream data rate falls below a downstream remove threshold.

29. The method of Claim 24, wherein the plurality of XDSL modems are located at a central office.

30. The method of Claim 24, wherein the number of XDSL modems is less than the number of twisted pair subscriber lines.

31. A method for segmenting a packet of data for communication by a plurality of XDSL modems, the method comprising:

receiving a packet;

5 determining the size of the packet; and

segmenting the packet into a plurality of subpackets based on a plurality of proportionality factors associated with a plurality of XDSL modems; and

communicating the subpackets using the XDSL modems.

10

32. The method of Claim 31, further comprising the step of addressing each subpacket to a different switched circuit.

15

33. The method of Claim 31, further comprising the step of modifying the proportionality factors in response to a modification in the number of XDSL modems to communicate the subpackets.

20

34. The method of Claim 31, further comprising the step of modifying the proportionality factors in response to a change in the data rate of an XDSL modem.

25

35. The method of Claim 31, wherein the proportionality factors for each XDSL modem further comprise:

an upstream proportionality factor; and

a downstream proportionality factor.

30

36. The method of Claim 31, wherein each proportionality factor comprises a ratio between the data rate of its associated XDSL modem and the sum of data rates of the XDSL modems.

1/6




FIG. 1

2/6




FIG. 2

3/6




FIG. 3

4/6

FIG. 4

200

	202 MODEM 1		204 MODEM 2		206 MODEM 3		208 MODEM 4		210 MODEM 5		212 MODEM 6		...
	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN	...
213 PACKET RATE (KMPs)	.062	.437	.112	.875	0.42	.398	-	-	0	.125	.100	.176	
214 BIT RATE (MBPS)	.5	3.5	.9	7	.4	3.2	-	-	0	1	0.7	1.3	
216 ERROR RATE $\times 10^{-7}$	0.3	0.1	0.9	0.9	1.1	0.3	-	-	0.2	0.05	0.1	0.0	
218 DATA RATE (MBPS)	.5	4	1	8	.5	4	1	8	.5	4	1	8	
220 ADD	80%	75%	85%	85%	70%	75%	90%	95%	85%	90%	75%	75%	
222 REMOVE	30%	35%	0%	0%	20%	25%	30%	30%	35%	30%	30%	30%	
224 PRIORITY	2		1		4		6		3		5		
226 MIN UP (SEC)	300		600		900		1200		900		600		
228 TIME UP (SEC)	103.7		588.2		137.6		-		43.2		82.4		
230 PROPORTION'TY FACTOR	0.25	0.25	0.5	0.5	0.33	0.33			0.25	0.25	0.67	0.67	
232 SESSION	1		1		2		-		1		2		
234 ROUTING ADDRESS													

76
LOADING
INFORMATION

78
THRESHOLD
INFORMATION

80
OPERATING
PARAMETERS


86
SESSION
INFORMATION

202A 202B 204A 204B 206A 206B 208A 208B 210A 210B 212A 212B

230

5/6

FIG. 5



6/6




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/US 98/05587

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04M11/06 H04L25/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04L H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 668 857 A (MCHALE JOHN F) 16 September 1997 cited in the application	24, 29, 30
Y	see column 1, line 46 - column 2, line 27; figure 1	31, 32, 36
A	see column 4, line 48 - column 5, line 22 see column 6, line 36 - column 7, line 28 see column 11, line 4-20; claim 1 --- -/--	1, 3, 4, 8, 10, 13, 16, 19, 22

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

7 October 1998

Date of mailing of the international search report

14/10/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Dupuis, H

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/05587

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 37458 A (NETSPEED INC) 9 October 1997	24, 29, 30
A	see page 3, line 14 - page 4, line 12 see page 12, line 20 - page 13, line 2 see page 15, line 31 - page 16, line 17 see page 23, line 13 - page 25, line 18 see page 43, line 24 - page 44, line 7 -----	1, 3, 4, 8, 10, 13, 16, 19, 22
Y	US 5 390 239 A (MORRIS GREGORY A ET AL) 14 February 1995 see abstract see column 2, line 48 - column 4, line 41 -----	31, 32, 36
A	US 5 546 379 A (MOON TIEN-JAN A ET AL) 13 August 1996 see column 1, line 64 - column 2, line 65 see column 3, line 47 - column 5, line 42 see column 15, line 12 - column 18, line 56 -----	1, 2, 7, 10, 14, 24, 25, 31

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/05587

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5668857	A	16-09-1997	AU 2426997 A	22-10-1997
			WO 9737458 A	09-10-1997
			US 5781617 A	14-07-1998
WO 9737458	A	09-10-1997	US 5668857 A	16-09-1997
			US 5781617 A	14-07-1998
			AU 2426997 A	22-10-1997
US 5390239	A	14-02-1995	NONE	
US 5546379	A	13-08-1996	US 5631897 A	20-05-1997
			JP 7107114 A	21-04-1995
			US 5678004 A	14-10-1997

1/6




FIG. 1

2/6




FIG. 2

3/6




FIG. 3

4/6

FIG. 4

200

	MODEM 1		MODEM 2		MODEM 3		MODEM 4		MODEM 5		MODEM 6		...
	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN	
76 PACKET RATE (KMPBS)	0.62	437	112	875	0.42	398	-	-	0	125	100	176	
76 BIT RATE (MBPS)	5	3.5	9	7	4	3.2	-	-	0	1	0.7	1.3	
76 ERROR RATE $\times 10^{-7}$	0.3	0.1	0.9	0.9	1.1	0.3	-	-	0.2	0.05	0.1	0.0	
78 DATA RATE (MBPS)	5	4	1	8	5	4	1	8	5	4	1	8	
78 ADD	80%	75%	85%	85%	70%	75%	90%	95%	85%	90%	75%	75%	
78 REMOVE	30%	35%	0%	0%	20%	25%	30%	30%	35%	30%	30%	30%	
80 PRIORITY	2		1		4		6		3		5		
80 MIN UP (SEC)	300		600		900		1200		900		600		
80 TIME UP (SEC)	103.7		588.2		137.6		-		43.2		82.4		
80 PROPORTIONTY FACTOR	0.25	0.25	0.5	0.5	0.33	0.33			0.25	0.25	0.67	0.67	
86 SESSION	1		1		2		-		1		2		
86 ROUTING ADDRESS	addr	addr	addr	addr	addr	addr	-	-	addr	addr	addr	addr	

202 204 206 208 210 212


213 214 216 218 220 222 224 226 228 230 232 234

230 202A 202B 204A 204B 206A 206B 208A 208B 210A 210B 212A 212B

230

5/6

FIG. 5



6/6




FIG. 6




FIG. 7